

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Material Name : Bitumen

CAS No : 8052-42-4

EC No : 232-490-9

Other Names of Product: Vacuum Resid, Bitumen 50/70, Bitumen 70/100, Bitumen 100/150, Bitumen 160/220.

1.2 Relevant identified uses of the substance or mixture and uses advised against
Industrial use, professional use.

1.3 Details of the supplier of the substance or mixture

Manufacturer/Supplier: Tüpraş

Adress : Türkiye Petrol Rafinerileri A.Ş. Genel Müdürlüğü KÖRFEZ/ KOCAELİ

Telephone : +90 262 316 30 00

Fax : +90 262 316 30 10-11

e-mail : selcen.temeltopallar@tupras.com.tr
yasin.ersoz@tupras.com.tr

1.4 Emergency Telephone Number

Company Telephone : +90 262 316 30 00

2. HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Skin Irrit. 2	H315
Eye Irrit. 2	H319

2.2 Label Elements

Labelling (Regulation (EC) No 1272/2008)



Symbols:

GHS07

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

Signal Word: Warning

Hazard statements: H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements:

Prevention : P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response : P362 Take off contaminated clothing and wash before reuse.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

Disposal : P501 Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations

2.3 Other hazards

No data available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance

CAS NO	EINECS NO	Chemical Composition	% Conc.	Risk Phreases (Regulation (EC) No 1272/2008)
8052-42-4	232-490-9	Bitumen or vacuum residue	0-100	H 315: Skin Irrit. 2 H319: Eye Irrit. 2
7783-06-4	231-977-3	Hydrogen sulfide	0.0001	H400: Aquatic Acute 1 H220: Falm. Gas 1 H330: Acute Tox. 2 H335: STOT SE 3 H410: Aquatic Chronic 1

NOTE: During storage or transit of hot bitumen, hydrogen sulfide may be generated.

3.2 Mixtures

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

Not applicable

4. FIRST-AID MEASURES

4.1 Description of First Aid Measures

Inhalation: If inhalation of mists, fumes or vapour causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist obtain medical advice.

Skin Contact:

Cold Product : Wash skin thoroughly with soap and water as soon as reasonably practicable. Remove heavily contaminated clothing and wash underlying skin.

Hot Product : Flood cold water to dissipate heat. Burns should be covered with clean cotton or gauze, and the casualty taken to hospital as soon as possible for examination and treatment.

Never use gasoline, kerosene or other solvents to remove bitumen from skin or clothing.

Eye Contact:

Cold Product : Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open. Obtain medical advice if any pain or redness develops or persists.

Hot Product : Flood with cold water to dissipate heat, if possible, ensuring eyelids are held open. Obtain medical attention immediately.

Ingestion: If contamination of the mouth occurs, wash out thoroughly with water. Except as a deliberate act, the ingestion of large amounts of product is unlikely. If it should occur, do not induce vomiting; obtain medical advice.

4.2 Most important symptoms/effects, acute & delayed

Inhalation: Harmful if inhaled. Casualties suffering ill effects as a result of exposure to hydrogen sulphide should be immediately removed to fresh air and medical assistance obtained without delay. Unconscious casualties must be placed in the recovery position. Monitor breathing and pulse rate and if breathing has failed, or is deemed inadequate, respiration must be assisted, preferably by the mouth to mouth method. Administer external cardiac massage if necessary. Seek medical attention immediately.

Skin: Where skin burns occur the area should be immediately immersed in cold water until the bitumen is thoroughly cooled.

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

4.3 Indication of immediate medical attention and special treatment needed

There are no specific antidotes or other therapeutic measures, treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Use alcohol resistant foam, dry powder, water spray and sand. DO NOT USE water jets.

5.2 Special hazards arising from substance or mixture

Combustion results from toxic gases. It can burn at high temperatures. Hazardous combustion products are carbon oxides, hydrogen sulfides, sulphur oxides.

5.3 Advice for fire-fighters

For major fires call the Fire Service. Ensure an escape path is always available from any fire.
Use

Use alcohol resistant foam, dry powder, water spray and sand. DO NOT USE water jets.

Fires in

confined spaces should be dealt with by trained personnel wearing approved breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure good ventilation. Wear protective clothing. Depending upon its temperature the product may be liquid, semi-solid or solid.

Protect drains from spills and prevent entry of product. This may in blockage on cooling

Scrape up bulk of solid material and remove remainder with sand or other suitable inert absorbent material.

Recovery of large spillages should be effected by specialist personnel. Spillages of hot product in confined spaces may be especially hazardous because highly toxic hydrogen sulphide gas may be present. For spillages in such confined spaces the use of approved breathing apparatus by personnel specially trained in its use may be required.

Vapour may collect in any confined space.

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In the event of spillages contact the appropriate authorities.

6.2 Environmental precautions

Do not allow to enter into ground water, surface water or drains.

6.3 Methods and material for containment and cleaning up

Recovery of large spillages should be effected by specialist personnel. Small and uncontained

spillages should be absorbed with liquid-binding material and collected in suitable containers for

disposal. Large spillages should be collected mechanically for disposal.

6.4 Reference to other sections

Refer to sections 8 and 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Ensure good ventilation and avoid as far as reasonably practicable the inhalation and contact with vapours. Use disposable cloths and discard when soiled. Do not put soiled cloths into pockets. Avoid contact with skin, eyes and clothes. Wash hands before breaks and immediately after using the product. Product may release hydrogen sulfide. A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product , tank waste and waste water.

7.2 Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with this product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Empty packages may contain some remaining product. Retain hazard warning labels on empty packages as a guide to the safe handling, storage and disposal of empty packaging. Do not enter storage tanks without breathing apparatus unless the tank

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

has been well ventilated and the tank atmosphere has been shown to contain hydrocarbon vapour concentrations of less than 1% of the lower flammability limit and an oxygen concentration of at least 20% volume. Confined spaces contaminated with hydrogen sulphide must always be considered as constituting potentially life threatening environments.

7.3 Specific end use

Except as provided in Section 1.2 is not required to offer any specific suggestions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Material	Exposure Limits
Bitumen or vacuum residue (CAS 8052-42-4)	No appropriate occupational exposure limits.
Hydrogen sulfide (CAS 7783-06-4)	ACGIH TLV/TWA : 10 ppm (8 hours) ACGIH TLV/STEL: 15 ppm (15 minutes)

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation.

8.2.2 Personal protective precautions

Personal protective equipment:

Eyes: Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Skin: Wear suitable protective clothing.

Inhalation: If operations are such that exposure to vapour, mist or fume may be anticipated, then suitable approved respiratory equipment should be worn. Note : Approved air-supplied breathing apparatus must be worn where there may be potential for inhalation of hydrogen sulphide gas.

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

	Test Unit	Guarantee	Test Method
Appearance		Black	Visual inspection
Odour		Petroleum	

	Test Unit	Guarantee	Test Method
Physical state		Semi-solid	
Flash point, min	°C	230	ASTM D 93
Sulphur, min	% wt	5	IP 336 or IP 242

9.2 Other Information

No relevant additional information available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Data is not available.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

10.4 Conditions to avoid

Data is not available.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Thermal decomposition products will vary with conditions. Overheating in storage may cause

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

partial vaporization and decomposition with the production of toxic hydrogen sulphide gas (H₂S).

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Eye contact: Will cause burns if hot material contacts eyes.

Skin contact: Will cause burns if hot material contacts skin. When product is heated to high temperatures vapours, mists or fumes will be given off and may condense, contaminating the skin. Prolonged or repeated skin contact may eventually result in dermatitis or more serious irreversible skin disorders.

Ingestion: Unlikely to cause harm if accidentally swallowed in small doses, larger quantities may cause nausea and diarrhoea.

Inhalation: May cause irritation to eyes, nose and throat at high vapour concentrations. May be toxic by inhalation when hydrogen sulphide is present in the vapour. Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Data is not available.

12.2 Persistence and degradability

This product is not biodegradable.

12.3 Bioaccumulative potential

This material is not expected to bio accumulate.

12.4 Mobility in soil

Spillages are unlikely penetrate the soil.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects

Data is not available.

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of by incineration or other suitable means under conditions approved by the local authority or via a licensed waste disposal contractor.

14. TRANSPORT INFORMATION

Land transport (ADR/RID):

ADR:

14.1 UN Number : 3257

14.2 UN proper shipping name : UN 3257, Elevated temperature liquid, n.o.s. (molten resin)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

14.5 Environmental hazards : Environmentally Hazardous:No

14.6 Special precautions for user : Refer to Chapter 7

Sea transport (IMDG Code):

14.1 UN Number : 3082

14.2 UN proper shipping name : UN 3257, Elevated temperature liquid, n.o.s. (molten resin)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

14.5 Marine pollutant : No

14.6 Special precautions for user : Refer to Chapter 7

Air transport (IATA):

Forbidden for transport on passenger and cargo aircraft in molten state.

15. REGULATORY INFORMATION

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The contents and format of this SDS are in accordance with EEC Commission Directive 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH).

15.2 National Regulations

This Safety Data Sheet, Environment and Urban Planning Ministry by December 13, 2014 date and 29204 numbered published in the Official Gazette of Hazardous Substances Regulation on safety data sheets of mixtures' Environment and Forestry and the Ministry of 26 by December 2008, and 27092 (bis) Official Gazette published "Classification of Hazardous Substances and preparations Regulations on Packaging and Labelling 'base is based.

16. OTHER INFORMATION

16.1 Other Information

The information presented about health, safety and environment issues in this safety data sheet was given by considering of best knowledge and reliable sources at the date of its preparation. Although maximum effort was shown, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practise any patented invention without a valid licence. The TÜPRAŞ shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.

Abbreviations :

ADN: Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin

This Safety Data Sheet is in accordance with Regulation (EC) No 1907/2006 (REACH).

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route

CLP: Classification, Labelling and Packaging Regulation according to 1272/2008/EC

IMDG: International Maritime Dangerous Goods

IATA: International Air Transport Association

IMDG = International Maritime Dangerous Goods Code

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

TWA: Time weighted average

STEL: Short-term exposure limit.

16.2 Related Person

Competent Person Accreditation no: TSE GBF-A-0-2828